



# SAFETY DATA SHEET

## Section 1 – Identification

**Product Name:** UV TOP COAT

**SDS Prepared:** 05-05-15

**SDS Updated:** N/A

**Revision:** 00

**Chemical Name:** Nail Lacquer

**Family:** Top Coat

**Product Use:** Nail Top Coat

**Product #:** 101199

**Distributed By:** Nail Alliance - Entity  
Gladstone, MO 64118

**Emergency Phone Number:** (800) 535-5053

**Information Contacts:** (714) 773-9758

## Section 2 – Hazards Identification

### EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- **Flammable liquid and vapor!**
- May cause allergic skin reaction.
- May cause eye irritation.
- May cause respiratory tract irritation.



### Potential Health Effects, Signs and Symptoms of Exposure:

**Primary Route of Entry** Inhalation, skin contact, eye contact

**Eye** Exposure causes eye irritation. Symptoms include stinging, tearing, redness and swelling.

**Skin** Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking, and skin burns.

**Ingestion** Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting.

**Inhalation** Vapor and mist are irritating to mucous membrane. Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits.

**Sub-Chronic Effects** It may cause headaches, nausea, vomiting and narcotic effect if over-exposed.

NOTE: Refer to Section 11, Toxicological Information for Details

## Section 3 – Composition/Information on Ingredients

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure	Limits	Carcinogen	%
				OSHA TWA/STEL	ACGIH TWA/STEL		
Acrylates Copolymer	25035-69-2	N/E	Acrylates Copolymer	N/E	N/E	Not Listed	35-45
n-Butyl Acetate	123-86-4	204-658-1	Butyl Acetate	150 ppm	150 ppm	Not Listed	25-35
Isobutyl Acetate	110-19-0	203-745-1	Isobutyl Acetate	150 ppm	150 ppm	Not Listed	20-30
2,5-thiophenediylbis(5-tert-butyl-1,3-benzoxazole)	7128-64-5	230-426-4	Bis(T-butyl benzoxazolyl) Thiophene	N/E	N/E	Not Listed	0-1
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI60725	N/E	N/E	Not Listed	0-1
N/E – None Established	N/DA – No Data Available						
N/R – Not Reviewed	N/A – Not Applicable						

**n-Butyl Acetate:** Hazard Symbol: N/E Risk Phrases: R10, R66, R67 Safety Phrases: S2, S25

**Isobutyl Acetate:** Hazard Symbol – F Risk Phrases – R11, R66 Safety Phrases – S2, S16, S23, S25, S29, S33

See Section 16 for Risk and Safety Phrase Key



# SAFETY DATA SHEET

## Section 4 – First Aid Measures

First Aid for Eye	If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.
First Aid for Skin	Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention.
First Aid for Inhalation	Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, seek medical attention.
First Aid for Ingestion	If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.

## Section 5 – Fire Fighting Measures

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
TAG Closed: 68°F/20°C	400 ppm	N/E

### Method:

Extinguishing Media:	Foam, dry chemical, cold water spray.
Fire Fighting Instructions:	Wear self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION. Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a safe distance and protected location.
Unusual Hazards:	Flammable. When exposed to heat and flame, material is a fire explosion hazard. It may produce toxic products CO, Carbon dioxide and oxides of nitrogen. Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.

## Section 6 – Accidental Release Measures

Spill or Release Procedures	Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.
-----------------------------	---

## Section 7 – Handling and Storage

Handling	Keep containers cool and dry. Keep away from heat, light and ignition sources. Avoid breathing high vapor concentrations. Avoid prolonged or repeated contact with skin. Use only with adequate ventilation. Wash thoroughly after handling.
Storage	Store in well ventilated area. Store @ 70°F +/- 15°F (21°C +/- 8°C), allow some air space above liquid level. Keep containers closed while not in use.
Explosion Hazard	Vapors are heavier than air and may travel along the ground or may be move by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product ( even just residue) can ignite explosively.

## Section 8 – Exposure Controls / Personal Protection

Engineering Controls	Facilities storing or utilizing this material should be equipped with an eye facility and safety shower. Use process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.
----------------------	---



# SAFETY DATA SHEET

## Personal Protective Equipment

### General

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

### Eye/ Face Protection

Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

### Skin Protection

Wear resistant gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

### Respiratory Protection

A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

## Section 9 – Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	VOC (g/L)	Specific Gravity	Viscosity	% Volatile
Blue to Violet, viscous liquid	fruity ester like odor	N/A	463	(H2O=1): 0.967	N/DA	W/W %: 99+

Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
170°F (77°C)	N/DA	N/DA	N/A	(Air=1): 1	N/A	N/A	Insoluble

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
TAG Closed: 68°F/20°C	400 ppm	N/E

## Section 10 – Stability and Reactivity

### Stability:

Stable

### Hazardous Decomposition Products:

Heated material produce NO<sub>2</sub>, CO<sub>2</sub>, CO

### Conditions to Avoid:

Heat, flame, ignition sources.

### Incompatibility (Materials to Avoid):

Avoid oxidizing agents, acids & bases (heat)

### Hazardous Polymerization:

Will not occur

## Section 11 – Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation – skin	Irritation – Eye
No information available	No information available	No information available	No information available	No information available

Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization	Mutagenicity	Sub-chronic Toxicity
No information available	No information available	No information available

## Section 12 – Ecological Information

### Ecotoxicological Information

Acute Toxicity To Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
No information available	No information available	No information available	No information available	No information available

### Chemical Fate Information

<b>Biodegradability</b>	No information available
-------------------------	--------------------------



# SAFETY DATA SHEET

<b>Chemical Oxygen Demand</b>	No information available
-------------------------------	--------------------------

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

## Section 13 – Disposal Considerations

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

## Section 14 – Transport Information

<b>DOT (49 CFR 172)</b>
Excepted Quantity ( 49 CFR -173.4a) (≤ 30 ml)
Consumer Commodity, ORM-D (≤ 1.0 L)
UN1263 Paint ,3,II (>1.0 L)
<b>IATA (DGR):128</b>
Excepted Quantity ( Air Shipper 4.1.2) (≤ 30 ml)
Consumer Commodity,9, ID8000 ( ≤ 0.5 L)
UN1263 Paint ,3,II (> 0.5 L)
<b>IMDG (OCN):</b>
Excepted Quantity (2008 IMO -3.5.1)) (≤ 30 ml)
UN1263 Paint ,3,II LTD QTY(≤ 1.0 L)
UN1263 Paint ,3,II (> 1.0 L)
<b>TDGR (Canadian GND):</b> Mark Package "Limited Quantity" or "Quantite Limitee" or "LTD QTY" or "Quant Ltee" (≤ 1.0 L); UN1263, Paint related material, 3, II, (>1.0 L)
<b>ADR/RID (EU):</b> UN 1263, Paint Related Material,3,II,ADR
<b>MEXICO (SCT):</b> UN1263, Pintura,3,II, Cantidad Limitada (≤ 1.0 L)
<b>ADGR(AUS):</b> UN1263, Paint, 3, II LTD QTY (≤ 1.0L)

## Section 15 – Regulatory Information

### US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAPs): <ul style="list-style-type: none"> <li>• NONE</li> </ul> There are no ODS's (ozone depleting substances) as defined by the U. S. Clean Air Act.
Clean Water Act: Priority Pollutant	This product contains the following Hazardous Substances as defined by the CWA: <ul style="list-style-type: none"> <li>• Isobutyl Acetate, CAS# 110-19-0 (HS)</li> <li>• Butyl Acetate, CAS# 123-86-4</li> </ul> Toluene can be found on the Priority Pollutant list. Toluene can be found on the Toxic Pollutant list per the CWA.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.



# SAFETY DATA SHEET

Occupational Safety and Health Act	This product is considered to be hazardous under the OSHA Hazard Communication Standard. Its hazard are: <ul style="list-style-type: none"> <li>• Immediate (acute) health hazard</li> <li>• Fire Hazard</li> </ul>
RCRA	This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261): <ul style="list-style-type: none"> <li>• May contain Characteristic of Ignitibility. RCRA Code: D001</li> </ul>
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Section 302 as extremely hazardous substances.
SARA Title III: Section 302 (RQ)	This product contains chemicals regulated under Section 302-304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List): <ul style="list-style-type: none"> <li>• Isobutyl Acetate, CAS# 110-19-0, RQ (Lbs): 5000</li> <li>• Butyl Acetate CAS#: 123-86-4, RQ(Lbs)5000</li> </ul>
SARA Title III: Section 311-312:	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: <ul style="list-style-type: none"> <li>• Immediate (acute) health hazard</li> <li>• Fire hazard</li> </ul>
SARA Title III: Section 313:	This product contains the following chemicals which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: <ul style="list-style-type: none"> <li>• None</li> </ul>
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.
TSCA Significant New Use Rule:	None of the chemicals in this material have a SNUR under TSCA.

## State Regulations

CA Right-to-Know Law: California No Significant Risk Level:	Isobutyl acetate CAS #110-19-0, Butyl Acetate CAS #123-86-4 NONE
MA Right-to-Know Law:	Isobutyl acetate CAS #110-19-0, Butyl Acetate CAS #123-86-4
NJ Right-to-Know Law:	Isobutyl acetate CAS #110-19-0, Butyl Acetate CAS #123-86-4
PA Right-to-Know Law:	Isobutyl acetate CAS #110-19-0, Butyl Acetate CAS #123-86-4
FL Right-to-Know Law:	Isobutyl acetate CAS #110-19-0, Butyl Acetate CAS #123-86-4
MN Right-to-Know Law:	Isobutyl acetate CAS #110-19-0, Butyl Acetate CAS #123-86-4

## International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	Isobutyl acetate CAS #110-19-0 is on the DSL list. Butyl Acetate CAS #123-86-4 is on the DSL list. WHMIS = B2, D1B, D2B 2,5-thiophenediylbis(5-tert-butyl-1,3-benzoxazole) CAS# 7128-64-5 is on the DSL List. WHMIS= n/da Acrylates Copolymer CAS # 25035-69-2 is on the DSL list. WHMIS = n/da D&C Violet #2 CAS# 81-48-1 is not considered to be a controlled product under WHMIS.
---	--

## Labeling according to EC directives – 1999/45/EC

European Community: 	<b>UV Acrylic Top Coat TF:</b> <ul style="list-style-type: none"> <li>• HAZARD SYMBOLS: <b>Xn, F:</b> Harmful, Highly Flammable</li> <li>• RISK PHRASES: <b>R11</b>, highly flammable, <b>R20/22:</b> Harmful by inhalation and if swallowed, <b>R36/37/38:</b> Irritating to eyes, respiratory system and skin</li> <li>• SAFETY PHRASES: <b>S7/9:</b> keep container tightly closed and in a well ventilated place, <b>S16:</b> keep away from sources of ignition- no smoking, <b>S24/25:</b> avoid contact</li> </ul>
---	---



# SAFETY DATA SHEET

with skin and eyes, **S33**: take precautionary measures against static discharges, **S37/39**: wear suitable gloves and eye/face protection, **S45**: In case of accident or if you feel unwell, seek medical advise immediately (show the label where possible)

## Section 16 – Other Information

### EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

**Hazard Symbol:**

Xn – Harmful substance or preparation  
F – Flammable substance or preparation

**Risk Phrases:**


R10 Flammable; R11 Highly flammable; R38 Irritating to skin; R41 Risk of serious damage to eyes; R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation; R63 Possible risk of harm to the unborn child; R65 Harmful: may cause lung damage if swallowed; R66 Repeated exposure may cause skin dryness or cracking; R67 Vapors may cause drowsiness and dizziness

**Safety Phrases:**


S2 Keep out of the reach of children; S25 Avoid contact with eyes; S36/37 Wear suitable protective clothing and gloves; S46 If swallowed, seek medical advice immediately and show this container or label; S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label

### Hazard Rating System (Pictograms)

NFPA:



HMIS:



The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This SDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the SDS may not be applicable. If there are any problems or concerns understanding this SDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.

Entity components are provided on an as is basis without warranties of any kind either expressed or implied. Entity does not warrant the use or the results of use of the materials sold on an as is basis since they are intended for remanufacturing or repackaging. It is the sole responsibility of the user to examine and determine appropriate application and regulatory requirements associated with said Entity components.