



Safety Data Sheet

Section 1: Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: Entity Gel-Lacquer Base Coat
Chemical Name: Nail Enamel

Product Use: cosmetics

Product # : 5201237

SDS Prepared: 2/23/2017
SDS Updated: 1/7/2021
Revision: 01

Manufactured By: Nail Alliance - North America, Inc
 1545 Moonstone, Brea, CA 92821

Emergency Phone Number: (800) 535-5053
Information Contacts: (714) 773-9758

Section 2: Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.



- Highly Flammable
- Prolonged inhalation may be harmful
- Can cause drowsiness, headaches, nausea, vomiting and narcosis
- May cause lung irritation

Potential Health Effects, Signs and Symptoms of Exposure:

Eye	Eye irritant both liquid and vapor
Skin	Mild skin irritant, can cause non-allergic contact dermatitis
Ingestion	Causes gastro-intestinal irritation, nausea, vomiting and diarrhea. Kidney damaged
Inhalation	Prolonged inhalation may be harmful Can cause drowsiness, headaches, nausea, vomiting and narcosis May cause lung irritation

NOTE: Refer to Section II, Toxicological Information for Details

Section 3: Composition/Information on Ingredients

INCI Name	CAS#	EINECS#	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Ethyl Acetate	141-78-6	205-500-4	400 ppm	400 ppm	Not Listed	25.0 - 35.0
Butyl Acetate	123-86-4	204-658-1	150 ppm	150ppm	Not Listed	20.0 - 30.0
Alcohol Denat.	64-17-5	200-578-6	1000 ppm	1000 ppm	Not Listed	10.0 - 25.0
Nitrocellulose	9004-70-0	N/A	N/E	N/E	Not Listed	1.0 - 15.0
Isopropyl Alcohol	67-63-0	200-661-7	400 ppm	400 ppm	Not Listed	1.0 - 10.0
Triphenyl Phosphate	115-86-6	204-112-2	3 mg/m3	3 mg/ m3	Not Listed	1.0 - 5.0

Ethyl Acetate	Hazard Symbol: F, Xi	Risk Phrases: R11, R36, R66, R67	Safety Phrases: S2, S16, S26, S33
Butyl Acetate	Hazard Symbol: F	Risk Phrases: R10, R66, R67	Safety Phrases: S2, S25
Alcohol Denat.	Hazard Symbol: F	Risk Phrases: R11	Safety Phrases: S2, S7, S16
Nitrocellulose	Hazard Symbol: F	Risk Phrases: R11	Safety Phrases: S2, S16, S33, S37/39
Isopropyl Alcohol:	Hazard Symbols: F, Xi	Risk Phrases: R11, R36, R67	Safety Phrases: S2, S7, S16, S24/25, S26
Triphenyl Phosphate	Hazard Symbol: Xn	Risk Phrases: R50, 53	Safety Phrases: S60, S61
N/E - None Established	N/DA - No Data Available	* See section 16	
N/R - Not Reviewed	N/A - Not Applicable		

Section 4: First Aid Measures

First Aid for Eye	Irrigate with copious amount of sterile water Seek medical attention immediately.
First Aid for Skin	Wash off with propriety remover, wash affected area with soap and water
First Aid for Inhalation	Remove person to fresh air. Seek medical attention
First Aid for Ingestion	Do not induce vomiting. SEEK IMMEDIATE MEDICAL ATTENTION

Section 5: Fire Fighting Measures

Flash Point (°F/ °C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
24°F / -4°C Estimated	No Data	No Data

WARNING: Highly Flammable. Keep away from heat, and any sources of ignition. Keep containers closed

Method:

Extinguishing Media:	Use carbon dioxide, foam or dry chemical for small fires; Water or foam extinguishers, water fog for large fires
Fire Fighting Instructions:	Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.

Section 6: Accidental Release Measures

Personal Precautions:	Use suitable protecting clothing/equipment eliminate all sources of ignition. No smoking
Methods of cleaning-up:	Contain spillage with earth or sand Mop-up small spills Sweep up, use sand or earth to absorb spill for large spillages
Environmental precautions:	Do not allow to enter water courses or drains Dispose in accordance with local regulations Local authorities should be advised if significant spillages cannot be contained

Section 7: Handling and Storage

Handling:	No smoking Prevent static discharges Exposure by inhalation or skin contact should be minimized by good industrial hygiene Vapor is heavier than air, spreads along the ground. Vapor can form an explosive mixture in air, prevalent in empty unclean vessels Use non-sparking utensils when handling this material
Storage:	Keep containers tightly closed when not in use. Store in a cool, dry place, away from sources of ignition, label containers Eliminate possible point ignition sources, e.g. No smoking, Naked flames, static discharges Use flame proof electrical equipment.

Section 8: Exposure Controls / Personal Protection

Engineering Controls When working with large quantities of product, provide adequate ventilation. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Exposure Levels:	Substance	OSHA-PEL-TWA	ACGIN-TLV-TWA
	Alcohol Denat.	1000 ppm	1000 ppm
	Butyl Acetate	150 ppm	150 ppm
	Ethyl Acetate	400 ppm	400 ppm
	Nitrocellulose	not established	not established
	Isopropyl Alcohol	400 ppm	200 ppm
	Triphenyl Phosphate	3 mg/m3	3 mg/m3

Personal Protective Equipment

General: Chemical goggles should be worn
Impervious gloves and overalls should also be worn
An approved respirator should be worn if the maximum exposure levels above are surpassed

Section 9: Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity	Vapor Density	
liquid	characteristic	NA	(H2O=1): 0.93- 0.98	N/DA	Heavier than air	
Boiling Point/Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Evaporation Rate	Ignition	Solubility In Water (20°C)
Undefined	N/A	N/A	N/A	No Data	No Data	Insoluble
Flash Point (°F/ °C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)				
24°F / -4°C Estimated	No Data	No Data				

Section 10: Stability and Reactivity

Stability: Stable under recommended storage conditions, affected by U.V., store away from direct sunlight.	Incapability (Material to Avoid): Peroxides, strong oxidizing agents, acids, alkalines and Peroxides
Hazardous Decomposition Products: Combustion of nitrocellulose may evolve nitrous oxid (poisonous) fumes CO, CO2, Nitrous Oxides, smoke.	Hazardous Polymerization: Will not occur
Conditions to Avoid: Flame, electric sparks, static and heat. Do not store at temperature over 120 °F Hazardous polymerization: will not occur	

Section 11: Toxicological Information

Organic solvents in the product may lead to removal of lipid soluble elements of the skin leading to non-allergic dermatitis upon repeated prolonged contact.
Vapors from solvents may cause; ill effect on then renal system; central nervous system problems; irritation to the respiratory tracks and other various mucosal membranes

Section 12: Ecological Information

This product should not be allowed to enter drains or water courses.
Used in large volumes, this product may incur the requirements of the Environmental Protection Act.

Ecotoxicological Information

Acute Toxicity to aquatic life	Acute Toxicity to plants and animals	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
No Information Available	No Information Available	No Information Available	No Information Available	No Information Available

Environmental Stability:

The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows

Ethyl Acetate:	Koc= 0.73. Water Solubility: 64,000 mg/l. Bioconcentration Factor= 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.
Butyl Acetate:	Koc= 1.8. Water Solubility: 120 Parts H2O at 25°C (77°F). Bioconcentration Factor= 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.
Isopropyl Alcohol:	Low Kow= 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days, Isopropyl alcohol is not expected to bioconcentrate.
Chemical Fate Information	
Biodegradability	No Information Available
Chemical Oxygen Demand	No Information Available

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated.
Do not allow to enter drinking water supplies, wastewater, or soil.

Section 13: Disposal Considerations

Waste disposal must be in accordance with appropriate Federal, State and local regulations.

Section 14: Transport Information

DOT (49 CFR -GND)

Excepted Quantity (49 CFR -173.4a) (≤ 30 ml)
Consumer Commodity, ORM-D (≤ 1.0 L)
UN1263 Paint ,3,11 (>1.0 L)

IATA (AIR):

Excepted Quantity (Air Shipper 4.1.2) (≤ 30 ml)
Consumer Commodity, 9, ID8000 (≤ 0.5 L)

UN1263 Paint ,3,II (> 0.5 L)

IMDG (OCN):

Excepted Quantity (2008 IMO -3.5.1)) (≤ 30 ml)

UN1263 Paint ,3,II LTD QTY(≤1.0 L)

UN1263 Paint ,3,II (> 1.0 L)

TDGR (Canadian GND):

Mark Package "Limited Quantity" or "Quantite Limitee" or "LTD QTY" or "Quant Ltee" (≤ 1.0 L)

UN1263, Paint related material, 3, II, (>1.0 L)

ADR/RID (EU):

UN 1263, Paint Related Material,3,II,ADR

MEXICO (SCT):

UN1263, Pintura,3,II, Cantidad Limitada (≤ 1.0 L)

ADGR(AUS):

UN1263, Paint, 3, II LTD QTY (≤ 1.0L)

Section 15: Regulatory Information

US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act: ● NONE This product does not contain any Class I or Class 2 ODS
Clean Water Act: Priority Pollutant	This product contains the following Hazardous Substances as defined by the CWA: ● NONE This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA
FDA:	This product complies with the appropriated sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics)
SARA Reporting Requirements:	SARA 304 (40 CFR Table 302.4)- Butyl Acetate, Ethyl Acetate
SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
TSCA Inventory Status:	This product contains chemicals listed on the TSCA inventory
CERCLA Reportable Quantity (RQ):	Butyl Acetate: 5000 lbs.; Ethyl Acetate: 5000 lbs.

State Regulations:

Ingredients in this mixture are found on the following state criteria list:

Proposition 65: None

CA Right-to-Know Law:	Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol
Delaware Air Quality Management List	Ethyl Acetate, Butyl Acetate, Nitrocellulose
Massachusetts Hazardous Substances List	Ethyl Acetate, Butyl Acetate, Nitrocellulose, Isopropyl Alcohol, Triphenyl Phosphate.
Minnesota Hazardous Substances List	Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol, Triphenyl Phosphate.
NJ Right-to-Know Law:	Isopropyl Alcohol
New York List of Hazardous Substances	Ethyl Acetate, Butyl Acetate
PA Right-to-Know Law:	Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol, Triphenyl Phosphate.
Washington Permissible Exposure Limits for Air Contaminates	Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol, Triphenyl Phosphate.
Wisconsin Hazardous Substances List	Ethyl Acetate

Section 16: Other Information

International Regulations:

Canadian Regulations:

Ethyl Acetate CAS# 141-78-6 is on the DSL list.WHMIS= B2,D2B

Butyl Acetate CAS # 123-86-4 is on the list. WHMIS + B2, D1B, D2B

This product has been classify according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL.

67/548/EU Requirements:

European Community:

The primary component of this product is listed in Annex I of the EU Directive 67/548/EEC



Ethyl Acetate: Flammable (F). R: 11-36/37/38 - Highly flammable. Irritating to eyes, reparatory system and skin. S: 2-16-23-29-33-
Keep out of the reach of children. Keep away from source of ignition - No smoking . Do not breathe gas, fumes, vapor or spray. Do not empty into drains.
Take precautionary measures against static discharges.

Butyl Acetate: Flammable (F). R: Flammable. S: 9-16-33- Keep container in a well -ventilated place. Keep away from sources of ignition. No smoking
Take precautionary measures against static discharges.

Isopropyl Alcohol: Flammable (F) . R 11-36/37- Highly flammable. Irritating to eyes, respiratory system and skin. S: 2-7-16-24/25/26
Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes,
rinse immediately with plenty of water and seek medical advice.

HAZCHEM CODE : 3[Y]E

EU Classes and Risk / Safety Phrases :

● **HAZARDOUS SYMBOLS:**

Xi - Irritants

F - Highly Flammable

Xn- Harmful

● **RISK PHRASES:**

R10 Flammable

R11 Highly Flammable

R20 Harmful by inhalation

R21 Harmful in contact with skin

R22 Harmful if swallowed

R36 Irritating to eyes

R37 Irritating to respiratory system

R38 Irritating to skin

R41 Risk of serious damage to eyes

R43 May cause sensitization by skin contact

R50 Very toxic to aquatic organisms

R53 May cause long-term adverse effects in the aquatic environment

R65 Harmful: may cause lung damage if swallowed

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapours may cause drowsiness and dizziness

● **SAFETY PHRASES:**

S16 Keep away from sources of ignition-No Smoking,

S23 Do no breathe vapor,

S25 Avoid contact with eyes

S29 Do not empty into drains

S33 Take precautionary measures against static discharges

Hazard Rating System (Pictograms)

NFPA:

Health ②

Flammability ③

Reactivity ①

HMS:

HEALTH	
FLAMMABILITY	
REACTIVITY	
PERSONAL PROTECTION	

This information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage use or disposal of the product. This SDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the SDS may not be applicable. If there are any problems or concerns understanding this SDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (1-800-535-5053).